



Blum-Awards
www.blum.com/award

MERIVOBX, BLUMOTION

Webcode
ID20288 ◀

Drawers, height N (space requirement 85.5 mm), load bearing class 40 kg

- Slim drawer side with characteristic shape, straight on the inside with flush cover cap
- Variety made easy, thanks to box platform concept
- Unique L-shape of cabinet profile for vertical stability with a high load bearing capacity of 40 kg
- Synchronised feather-light glide and high front stability for new possibilities in furniture design
- Integrated BLUMOTION soft-close system, interface for SERVO-DRIVE, TIP-ON BLUMOTION and side stabilisation
- Fast, tool-free assembly of front, convenient 3-dimensional front adjustment

Product overview

Drawer suitable for Blum MERIVOBX.

Double walled drawer sides in

- a) Steel in silk white matt
- b) Steel in indium grey matt
- c) Steel in orion grey matt

Optionally with individual branding element on the outside of the drawer sides. Cabinet profiles with low-friction cylindrical nylon rollers and synchronised carriage system. Integrated BLUMOTION for silent and effortless closing action.

Cabinet profiles and drawer sides in nominal length and load bearing class

- a) 400 mm, 40 kg
- b) 450 mm, 40 kg
- c) 500 mm, 40 kg
- d) 550 mm, 40 kg

Dynamic carrying capacity: 100,000 opening and closing cycles with selected nominal length and load bearing class. Can optionally be equipped with electric opening support system.

Option of combining with side stabiliser. Fast, tool-free assembly of front. Three-dimensional front adjustment. Optional use with Blum "CABLOXX" locking system (ID20267). Optional use with Blum fixing system "EXPANDO T" (ID20279) for thin fronts measuring 8 mm and above.

Equipment options

- ▶ ID20144 SERVO-DRIVE for box systems



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"
www.blum.com/catalogue