

Memo

CLIP top BLUMOTION 155°

Packed with functionality

CLIP top BLUMOTION 155° –

0-protrusion hinge for overlay application

The benefits of CLIP top BLUMOTION are integrated into the wide angle hinge with 0-protrusion. The simple appearance provides a perfect combination of the easy, 3-dimensional front adjustment and the usual high quality of motion. CLIP top BLUMOTION 155° features an integrated soft-close mechanism and is suitable for special applications, e.g. mitred applications.

High quality down to the last detail



BLUMOTION is integrated into the hinge arm



Switch for BLUMOTION deactivation



INSERTA for tool-free assembly of the boss



Matching boss cover caps – also in onyx black

www.blum.com

 **blum**®

Ordering information

Overlay application			
Boss		INSERTA	
Hinge	Spring	Colour	
CLIP top BLUMOTION	●	NI ONS	71B7590
CLIP top	●	NI	71T7590
CLIP top	○	NI ONS	70T7590.TL

Boss		Screw-on	
Hinge	Spring	Colour	
CLIP top BLUMOTION	●	NI ONS	71B7550
CLIP top	●	NI	71T7550
CLIP top	○	NI ONS	70T7550.TL

Boss		Knock-in	
Hinge	Spring	Colour	
CLIP top BLUMOTION	●	NI ONS	71B7580
CLIP top	●	NI	71T7580

Half overlay application			
Boss		INSERTA	
Hinge	Spring	Colour	
CLIP top BLUMOTION	●	NI ONS	71B7690
CLIP top	○	NI	70T7690.TL

Boss		Screw-on	
Hinge	Spring	Colour	
CLIP top BLUMOTION	●	NI ONS	71B7650
CLIP top	●	NI	71T7650
CLIP top	○	NI	70T7650.TL

Inset application	
For inset application use hinges for half overlay application and a 9 mm spaced mounting plate	

Accessories		
Hinge boss spacing		
Hinge	Spacing (mm)	
CLIP top BLUMOTION	1.5	70T3507.21
CLIP top	1.5	70T3507.21

		Hinge arm cover cap	
Printing / Embossing	Logo	Colour	
Plain	–	NI ONS	70.4503
Embossed	Blum	NI	70.4503.BP

		Hinge boss cover cap	
Hinge	Colour		
CLIP top BLUMOTION	NI ONS		70T7504
CLIP top	NI ONS		70T7504

		Opening angle stop	
Opening angle	Colour		
92°	Dark grey		70T7553.09
110°	RAL 7037 dust grey		70T7553

		Insertion ram	
Colour	Material		
Orange	Nylon		MZM.0040

		Chipboard screw	
Ø (mm)	Length (mm)		
3.5	15		609.1500
3.5	17		609.1700

Note	
A trial application is recommended when combining CLIP top BLUMOTION hinges and CLIP top hinges with springs on small, light fronts up to 300 mm wide. It is recommended to use only one hinge type for wider fronts.	

- With spring
- Unsprung
- NI Nickel plated
- ONS Onyx black