



AVENTOS HS

Webcode
ID20002 ◀

for up & over lift systems

- Ideal for large-area and single fronts
- Can also be used with wall cabinets with cornice or crown moulding
- Easy opening, variable stop and silent and effortless closing thanks to the integrated BLUMOTION dampening
- Harmonious gap design thanks to convenient 3-dimensional front adjustment
- Fast assembly and removal of the front using CLIP technology

Product overview

Blum AVENTOS HS for up & over lift systems. Up & over lift fitting. For wooden fronts, wide and narrow alu frames and thin fronts measuring 8 mm and above. Symmetrical lift mechanism with spring package. Lift system can be stopped in any position using infinitely variable lift mechanism adjustment. High stability with wide and large-area fronts via cross stabiliser. Integrated opening and closing dampening. Removable lever arm. Simple, tool-free fast installation of the front using clip-on assembly method. Lift mechanism can be attached to the cabinet side before assembly. No parts projecting beyond the cabinet side. Can be combined with an electrical motion support system. For cabinet heights of 350 to 800 mm. For cabinet widths up to 1,800 mm.

3-dimensional front adjustment: Height ± 2 mm, Side ± 2 mm, Depth ± 2 mm.

Straightforward, minimalist cover cap made of nylon in light grey, silk white or dark grey

- a) silk white
- b) light grey
- c) Dark grey

Optional use with Blum fixing system "EXPANDO T" (ID20279) for thin fronts measuring 8 mm and above.

Equipment options

- ID20141 SERVO-DRIVE for AVENTOS HS



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"
www.blum.com/catalogue