





red<mark>dot</mark> design award winner 2008



Blum-Awards www.blum.com/award

# **AVENTOS HL**

Webcode ID20003 ◀

### for lift ups

- Well-suited to small-area, single fronts
- Ideal for applications in high or wall cabinets with fronts above as well as recessed cabinets
- Easy opening, variable stop and silent and effortless closing thanks to the integrated BLUMOTION dampening
- Harmonious gap design thanks to convenient 3-dimensional front adjustment
- Fast assembly and removal of the front using CLIP technology

#### **Product overview**

Blum AVENTOS HL for lift ups. Parallel lift up fitting. For wooden fronts, wide and narrow alu frames, mitred and rebated applications, as well as thin fronts measuring 8 mm and above. Symmetrical lift mechanism with spring package. Lift system can be stopped in any position using infinitely variable lift mechanism adjustment. High stability with wide and large-area fronts via cross stabiliser. Integrated opening and closing dampening. Removable lever arm. Simple, tool-free fast installation of the front using clip-on assembly method. Lift mechanism can be attached to the cabinet side before assembly. No parts projecting beyond the cabinet side. Can be combined with an electrical motion support system. For cabinet heights of 300 to 580 mm. For cabinet widths up to 1,800 mm. 3-dimensional front adjustment: Height  $\pm$  2 mm, Side  $\pm$  2 mm, Depth  $\pm$  2 mm.

Straightforward, minimalist cover cap made of nylon in light grey, silk white or dark grey

- a) silk white
- b) light grey
- c) Dark grey

Optional use with Blum fixing system "EXPANDO T" (ID20279) for thin fronts measuring 8 mm and above.

#### **Equipment options**

▶ ID20142 SERVO-DRIVE for AVENTOS HL



## Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning" www.blum.com/catalogue

