



reddot design award
winner 2007



German
Design Award
SPECIAL
MENTION 2013



Blum-Awards
www.blum.com/award

TANDEMBOX intivo, BLUMOTION

Webcode
ID20028 ◀

Drawer, height N (Space requirement 82.5 mm), load bearing class 30 kg

- Drawer for TANDEMBOX intivo
- Integrated BLUMOTION for soft and effortless closing action
- Smooth running action
- Fast, tool-free assembly of front
- Two-dimensional front adjustment

Product overview

Drawer suitable for Blum TANDEMBOX intivo.

Double walled drawer sides in

a) Steel in silk white

With cover caps for drawer sides. Concealed, guided full extension with low-friction cylindrical nylon roller runners and integrated BLUMOTION.

Cabinet profiles and drawer sides in nominal length and load bearing class

a) 400 mm, 30 kg

b) 450 mm, 30 kg

c) 500 mm, 30 kg

d) 550 mm, 30 kg

Dynamic carrying capacity: 100,000 opening and closing cycles with 30 kg total load. Can optionally be equipped with electric opening support system. Option of combining with side stabiliser. Fast, tool-free assembly of front. Two-dimensional front adjustment. Optional use with Blum "CABLOXX" locking system (ID20267). Optional use with "SPACE STEP" (ID20285).

Equipment options

- ▶ ID20144 SERVO-DRIVE for box systems LEGRABOX and TANDEMBOX
- ▶ ID20331 myLEGRABOX – LEGRABOX pure, LEGRABOX free



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"
www.blum.com/catalogue