



reddot design award  
winner 2007



German  
Design Award  
SPECIAL  
MENTION 2013



Blum-Awards  
[www.blum.com/award](http://www.blum.com/award)

# TANDEMBOX intivo, BLUMOTION

Webcode  
ID20030 ◀

**Drawer, height M (Space requirement 98.5 mm), load bearing class 30/65 kg**

- Drawer for TANDEMBOX intivo
- Integrated BLUMOTION for soft and effortless closing action
- Smooth running action
- Fast, tool-free assembly of front
- Two-dimensional front adjustment

## Product overview

Drawer suitable for Blum TANDEMBOX intivo.

Double walled drawer sides in

a) Steel in silk white

With cover caps for drawer sides. Concealed, guided full extension with low-friction cylindrical nylon roller runners and integrated BLUMOTION.

Cabinet profiles and drawer sides in nominal length and load bearing class

- a) 270 mm, 30 kg
- b) 300 mm, 30 kg
- c) 350 mm, 30 kg
- d) 400 mm, 30 kg
- e) 450 mm, 30/65 kg
- f) 500 mm, 30/65 kg
- g) 550 mm, 30/65 kg
- h) 600 mm, 30/65 kg
- i) 650 mm, 65 kg

Dynamic carrying capacity: 100,000 opening and closing cycles with selected nominal length and load bearing class. Can optionally be equipped with electric opening support system. Option of combining with side stabiliser. Fast, tool-free assembly of front. Two-dimensional front adjustment. Appropriate ORGA-LINE inner dividing system available as an option. Optional use with Blum "CABLOXX" locking system (ID20267). Optional use with "SPACE STEP" (ID20285).

## Equipment options

- ▶ ID20144 SERVO-DRIVE for box systems LEGRABOX and TANDEMBOX
- ▶ ID20151 ORGA-LINE for drawers



## Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"  
[www.blum.com/catalogue](http://www.blum.com/catalogue)