



reddot design award
winner 2007



product
design
award

2007



Blum-Awards
www.blum.com/award

TANDEMBOX intivo, BLUMOTION

Webcode
ID20036 ◀

Inner pull-out with **BOXCOVER**, height D (Space requirement 224 mm), load bearing class 30/65 kg

- Closed inner pull-out without gallery
- Endless design options thanks to lateral design elements made from any desired material
- Seamless transition from drawer side to design element
- All components feature homogeneous use of materials and colours
- Integrated BLUMOTION for soft and effortless closing action
- Smooth running action

Product overview

Blum TANDEMBOX intivo inner pull-out.

Double walled drawer sides in

a) Steel in silk white

With cover caps for drawer sides. Concealed, guided full extension with low-friction cylindrical nylon roller runners and integrated BLUMOTION.

Cabinet profiles and drawer sides in nominal length and load bearing class

- a) 270 mm, 30 kg
- b) 300 mm, 30 kg
- c) 350 mm, 30 kg
- d) 400 mm, 30 kg
- e) 450 mm, 30/65 kg
- f) 500 mm, 30/65 kg
- g) 550 mm, 30/65 kg
- h) 600 mm, 30/65 kg
- i) 650 mm, 65 kg

Dynamic carrying capacity: 100,000 opening and closing cycles with selected nominal length and load bearing class. Can optionally be equipped with electric opening support system. Option of combining with side stabiliser. Fast, tool-free assembly of front. Appropriate ORGA-LINE inner dividing system available as an option.

Equipment options

- ▶ **ID20154** Design elements for TANDEMBOX intivo
- ▶ **ID20144** SERVO-DRIVE for box systems LEGRABOX and TANDEMBOX
- ▶ **ID20152** ORGA-LINE for pull-outs



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"
www.blum.com/catalogue

blum®