





design award winner



www.blum.com/award

TANDEMBOX plus, BLUMOTION

Webcode ID20085 <

Inner pull-out with gallery, height C (Space requirement 192 mm), load bearing class 30/65 kg

- Inner pull-out with round gallery
- All nylon parts in dust grey
- Integrated BLUMOTION for soft and effortless closing action
- Smooth running action

Product overview

Blum TANDEMBOX plus inner pull-out. Double walled drawer sides in

- a) Steel in white
- b) Steel in white aluminium (RAL9006)

With cover caps for drawer sides. Concealed, guided full extension with low-friction cylindrical nylon roller runners and integrated BLUMOTION.

Cabinet profiles and drawer sides in nominal length and load bearing class

- a) 350 mm, 30 kg
- b) 400 mm, 30 kg
- c) 450 mm, 30/65 kg
- d) 500 mm, 30/65 kg
- e) 550 mm, 30/65 kg f) 600 mm, 30/65 kg
- g) 650 mm, 65 kg

Dynamic carrying capacity: 100,000 opening and closing cycles with selected nominal length and load bearing class. Can optionally be equipped with electric opening support system.

Option of combining with side stabiliser. Fast, tool-free assembly of front. Appropriate ORGA-LINE inner dividing system available as an option.

Equipment options

- ▶ ID20144 SERVO-DRIVE for box systems LEGRABOX and TANDEMBOX
- ▶ ID20152 ORGA-LINE for pull-outs



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning" www.blum.com/catalogue

