



reddot design award
winner 2012



Blum-Awards
www.blum.com/award



LEGRABOX, TIP-ON BLUMOTION

Webcode
ID20204 ◀

Drawers, height N (space requirement 80 mm), load bearing class 40/70 kg

- Slimline design with 12.8 mm drawer side thickness
- Elegant appearance and clear lines thanks to accent lines on the outside of the drawer sides
- Straight interior and exterior drawer sides
- Opens with a light touch, has a feather-light glide and closes silently and effortlessly – 100% mechanically
- Exact front spacing due to convenient 3-dimensional front setting
- 2.5 mm front gap for optimum function.

Product overview

Drawer suitable for Blum LEGRABOX.

Double walled drawer sides in

- a) Steel in silk white matt
- b) Steel in orion grey matt
- c) Steel in carbon black matt
- d) Anti-fingerprint stainless steel

Optionally with individual branding element on the outside of the drawer sides. Cabinet profiles with low-friction cylindrical nylon rollers and synchronised carriage system. Opens with just a touch, has a feather-light glide and closes softly and effortlessly, 100% mechanically with TIP-ON BLUMOTION technology. It is possible to pull to open and push to close. Synchronisation available as an option.

Cabinet profiles and drawer sides in nominal length and load bearing class

- a) 400 mm, 40 kg
- b) 450 mm, 40/70 kg
- c) 500 mm, 40/70 kg
- d) 550 mm, 40/70 kg

Dynamic carrying capacity: 100,000 opening and closing cycles with 40 kg total load. Option of combining with side stabiliser. Fast, tool-free assembly of front. Three-dimensional front adjustment. Optional use with Blum "CABLOXX" locking system (ID20267). Optional use with Blum fixing system "EXPANDO T" (ID20279) for thin fronts measuring 8 mm and above. Optional use with "SPACE STEP" (ID20285).

Equipment options

- ▶ ID20264 TIP-ON BLUMOTION for LEGRABOX
- ▶ ID20331 myLEGRABOX – LEGRABOX pure, LEGRABOX free



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning"
www.blum.com/catalogue