







Blum-Awards www.blum.com/award

# TANDEMBOX intivo, TIP-ON BLUMOTION

Webcode ID20226 ◀

## Drawer, height M (Space requirement 101.5 mm), load bearing class 30/65 kg

- Drawer for TANDEMBOX intivo
- Opens with a light touch, has a feather-light glide and closes silently and effortlessly 100% mechanically
- 2.5 mm front gap for optimum function.
- Fast, tool-free assembly of front
- Three-dimensional front adjustment

### **Product overview**

Drawer suitable for Blum TANDEMBOX intivo. Double walled drawer sides in

a) Steel in silk white

With cover caps for drawer sides. Concealed, guided full extension with low-friction cylindrical rollers. Opens with just a touch, has a feather-light glide and closes softly and effort-lessly, 100% mechanically with TIP-ON BLUMOTION technology. It is possible to pull to open and push to close. Synchronisation available as an option.

Cabinet profiles and drawer sides in nominal length and load bearing class

- a) 270 mm, 30 kg
- b) 300 mm, 30 kg
- c) 350 mm, 30 kg
- d) 400 mm, 30 kg

- e) 450 mm, 30/65 kg
- f) 500 mm, 30/65 kg
- g) 550 mm, 30/65 kg
- h) 600 mm, 30/65 kg
- i) 650 mm, 65 kg

Dynamic carrying capacity: 100,000 opening and closing cycles with selected nominal length and load bearing class. Option of combining with side stabiliser. Fast, tool-free assembly of front. Three-dimensional front adjustment. Appropriate ORGA-LINE inner dividing system available as an option. Optional use with Blum "CABLOXX" locking system (ID20267). Optional use with "SPACE STEP" (ID20285).

# **Equipment options**

- ▶ ID20265 TIP-ON BLUMOTION for TANDEMBOX
- ▶ ID20151 ORGA-LINE for drawers



### **Further information**

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning" www.blum.com/catalogue

