





2007



Blum-Awards www.blum.com/award

# **TANDEMBOX** intivo, **TIP-ON BLUMOTION**

Webcode

High fronted pull-out with BOXCOVER, height D (Space requirement 227 mm), load bearing class 30/65 kg

- Closed high-fronted pull-out without gallery
- Endless design options thanks to lateral design elements made from any desired material
- Seamless transition from drawer side to design element
- All components feature homogeneous use of materials and colours
- Opens with a light touch, has a feather-light glide and closes silently and effortlessly 100% mechanically
- Harmonious gap layout thanks to convenient four-dimensional front adjustment

#### **Product overview**

Blum TANDEMBOX intivo high fronted pull-out.

- Double walled drawer sides in
- a) Steel in silk white

With cover caps for drawer sides. Concealed, guided full extension with low-friction cylindrical rollers. Opens with just a touch, has a feather-light glide and closes softly and effortlessly, 100% mechanically with TIP-ON BLUMOTION technology. It is possible to pull to open and push to close. Synchronisation available as an option.

Cabinet profiles and drawer sides in nominal length and load bearing class

- a) 270 mm, 30 kg
- b) 300 mm, 30 kg
- c) 350 mm, 30 kg
- d) 400 mm, 30 kg
- e) 450 mm, 30/65 kg
- f) 500 mm, 30/65 kg

#### g) 550 mm, 30/65 kg

- h) 600 mm, 30/65 kg
- i) 650 mm, 65 kg

Dynamic carrying capacity: 100,000 opening and closing cycles with selected nominal length and load bearing class. Option of combining with side stabiliser. Fast, tool-free assembly of front. Four-dimensional front adjustment. Appropriate ORGA-LINE inner dividing system available as an option. Optional use with Blum "CABLOXX" locking system (ID20267).

### **Equipment options**

- ID20154 Design elements for TANDEMBOX intivo
- ID20265 TIP-ON BLUMOTION for TANDEMBOX
- ID20152 ORGA-LINE for pull-outs



#### **Further information**

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning" www.blum.com/catalogue

## ID20228 <

