







www.blum.com/award

CLIP top BLUMOTION hinge for thin doors 110°

Webcode ID20276 <

for thin doors from 8 to 14 mm

- EXPANDO T fixing system for a variety of front materials
- Front thicknesses from 8 mm to 14 mm
- Integrated BLUMOTION for soft and effortless closing action
- Hinge without door protrusion for overlay application (for cabinets with inner pull-outs or pull-out surrounds)
- Deactivation option for BLUMOTION dampening for small, lightweight doors
- Harmonious gap layout thanks to convenient and infinitely variable 3-dimensional adjustment
- Tool-free fast assembly and removal of the door via tried and trusted CLIP mechanism

Product overview

Blum CLIP top BLUMOTION hinge for thin doors 110°. Hinge for thin doors from 8 to 14 mm. Hinge without door protrusion enables the implementation of furniture with inner pull-outs or pull-out surrounds. 110° opening angle.

Finishes available

- a) nickel plated
- b) Onyx black

Integrated soft closing in the hinge arm; can be deactivated. Tool-free fast assembly and removal of the door on the cabinet using clip-on assembly method. Third location pin in hinge arm for stable hold of the hinge on the mounting plate. Infinitely variable 3-dimensional adjustment: Height max. ± 3 mm, Side ± 2 mm, Depth adjustment via spiral screw + 3/- 2 mm.

Optionally with cover caps for hinge arm.

Optionally with

- a) 85° opening angle stop
- b) 92° opening angle stop

Assembly on

- a) horizontal mounting plate
- b) cruciform mounting plate

With EXPANDO T fixing system for thin fronts. Optional use with Blum fixing system "EXPANDO T" (ID20279) for thin fronts measuring from 8 mm to 14 mm.

Equipment options

▶ ID20279 EXPANDO T – fixing system for thin fronts measuring 8 mm and above



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning" www.blum.com/catalogue

