

Webcode

ID20309 <

MERIVOBOX modular with gallery, TIP-ON BLUMOTION

Inner pull-out with high design element, height E (space requirement 207 mm), load bearing class 40/70 kg

- Slim drawer side with characteristic shape, straight on the inside with flush cover cap
- Variety made easy, thanks to box platform concept
- Unique L-shape of cabinet profile for vertical stability with a high load bearing capacity of 40/70 kg
- Synchronised feather-light glide and high front stability for new possibilities in furniture design
- Opens with a light touch, has a feather-light glide and closes silently and effortlessly 100% mechanically
- Fast, tool-free assembly of front, convenient 3-dimensional front adjustment

Product overview

Inner pull-out suitable for Blum MERIVOBOX.

- Double walled drawer sides in
- a) Steel in silk white matt
- b) Steel in indium grey matt
- c) Steel in orion grey matt

Optionally with individual branding element on the outside of the drawer sides. Cabinet profiles with low-friction cylindrical nylon rollers and synchronised carriage system. Opens with just a touch, has a feather-light glide and closes softly and effortlessly, 100% mechanically with TIP-ON BLUMOTION technology. It is possible to pull to open and push to close. Synchronisation available as an option.

Cabinet profiles and drawer sides in nominal length and load bearing class

- a) 270 mm, 40 kg
- b) 300 mm, 40 kg
- c) 350 mm, 40 kg
- d) 400 mm, 40 kg
- e) 450 mm, 40/70 kg

Equipment options

- ID20322 TIP-ON BLUMOTION for MERIVOBOX
- ID20198 AMBIA-LINE for drawers

- f) 500 mm, 40/70 kg
- g) 550 mm, 40/70 kg
- h) 600 mm, 40/70 kg

Dynamic carrying capacity: 100,000 opening and closing cycles with selected nominal length and load bearing class. Option of combining with side stabiliser. Fast, tool-free assembly of front. Three-dimensional front adjustment. Optionally with appropriate inner dividing system AMBIA-LINE. Optional use with Blum "CABLOXX" locking system (ID20267). Optional use with Blum fixing system "EXPANDO T" (ID20279) for thin fronts measuring 8 mm and above.



Further information

In the print version of the Blum catalogue or online in the Blum browse catalogue under "Planning" www.blum.com/catalogue

