AVENTOS HK-S

The ideal choice for small stay lifts





With AVENTOS HK-S, there is now a scaled down lift system that is specially designed for stay lift applications on smaller fronts. It is therefore perfectly suited to the cabinets positioned at the top of larder units and over appliances. AVENTOS HK-S completes the existing lift system programme which includes the bi-fold lift system (HF), up & over lift system (HS), lift up (HL) and stay lift (HK).

Opening and closing: approved comfort




AVENTOS HK-S customers will also benefit from the high levels of comfort that come from integrated BLUMOTION for silent and effortless closing. As with all members of the AVENTOS family the variable stop ensures that the frontal will hold open at any desired position.

Ideal performance aesthetically covered

AVENTOS HK-S is optimally designed for the requirements of small stay lifts:

- For cabinet heights up to max. 400 mm
- Cabinet width depends on the power factor



Compared to AVENTOS HK, AVENTOS HK-S is considerably smaller. This ensures that the lift mechanism fits harmoniously into smaller cabinets.

Less effort for assembly and adjustment



The symmetrical lift mechanism can be used on the left or right.



Tool-free front assembly to the lift mechanism using CLIP technology.



Fronts can be adjusted in 3 dimensions to ensure perfect gap alignment.



The lift mechanisms can be adjusted to the respective door weight using a cordless screwdriver.



Warning

Please note the safety information on AVENTOS fittings.



Order specification

Power factor = cabinet height [mm] x door weight including double the handle weight [kg]

2 x 20K2E01

LF 960-2.040

2 x 20K2C01 LF 400-1.000

1 x 20K2A01 + 1 x 20K2C01 LF 220-500

LF Power factor

Lift mechanism two-sided

A trial application is recommended when you are in a borderline area of the individual lift mechanism.

Price information



| AVENTOS HK-S set (Cabinet height: up to 400 mm) | | | | | |
|---|--------------|-----|-----------------|--|--|
| Article No. | Power factor | QTY | Price per piece | | |
| 20K2A01 | 220 - 500 | 2 | S\$ 17.46 | | |
| 20K2C01 | 400 - 1000 | 2 | S\$ 17.46 | | |
| 20K2E01 | 960 - 2040 | 2 | S\$ 17.46 | | |
| Power factor: cabinet height [mm] x front weight including two handles [kg] | | | | | |



| Front fixing brackets | | | | |
|-----------------------|-----------------------|-----|-----------------|--|
| Article No. | Description | QTY | Price per piece | |
| 20K4A01 | For wooden doors | 2 | S\$ 1.42 | |
| 20K4A01A | For narrow alu frames | 2 | S\$ 5.10 | |



| Cover caps | | | | |
|-------------|---------------|-----|-----------------|--|
| Article No. | Description | QTY | Price per piece | |
| 20K8A01 | Grey or white | 2 | S\$ 2.40 | |

Optional items



| Opening angle stop | | | | |
|--------------------|---------------|-----|-----------------|--|
| Article No. | Opening angle | QTY | Price per piece | |
| 20K7011 | 75° | 1 | S\$ 0.92 | |
| 20K7041 | 100° | 1 | S\$ 0.92 | |

Prices are subject to change without prior notice. Please contact Blum for verification.